

CONTROL ACCESSORY SELECTION GUIDE

Product Family	Type	Power (W/m)	Max Run Length (m)	Max Run Power (W)	Starter Cable/ Terminator	Suggested Control Equipment			
						Switched	0-10V PWM	DALI 2	DMX
Flexi-Line (S & T)	Static White	6	9.6	57.6	2-Way (JWPF), 2000mm	HLG80H-24	PSU-PWM-60-24	LCA-60-24V	
	Static White	10	4.8	48	2-Way (JWPF), 2000mm	HLG80H-24	PSU-PWM-60-24	LCA-60-24V	
	Static White	15	4.8	72	2-Way (JWPF), 2000mm	HLG80H-24	PSU-PWM-90-24	LCA-100-24V	
	Tunable White	15	4.8	72	3-Way (JWPF), 2000mm			HLG80H-24 + LIN220D	HLG80H-24 + Hybrid Drive 6
	RGB	15	4.8	72	4-Way (JWPF), 2000mm				HLG80H-24 + Hybrid Drive 6
	RGB Dynamic	15	4.8	72	3-Way (JWPF), 1000mm				HLG80H-24 + Hybrid Drive 6
Flexi-Line (S)	RGBW	15	4.8	72	6-Way (JWPF), 2000mm				HLG80H-24 + Hybrid Drive 6
Flexi-Miniline	Static White	6	9.6	57.6	2-Way (JWPF), 2000mm	HLG80H-24	PSU-PWM-60-24	LCA-60-24V	
	Static White	10	4.8	48	2-Way (JWPF), 2000mm	HLG80H-24	PSU-PWM-60-24	LCA-60-24V	
	Static White	15	4.8	72	2-Way (JWPF), 2000mm	HLG80H-24	PSU-PWM-90-24	LCA-100-24V	
	Tunable White	15	4.8	72	3-Way (JWPF), 2000mm			HLG80H-24 + LIN220D	HLG80H-24 + Hybrid Drive 6
	RGB	15	4.8	72	4-Way (JWPF), 2000mm				HLG80H-24 + Hybrid Drive 6
	RGB Dynamic	15	4.8	72	3-Way (JWPF), 1000mm				HLG80H-24 + Hybrid Drive 6
Flexi-Light	Static White	15	4.8	72	2-Way (JWPF), 2000mm	HLG80H-24	PSU-PWM-90-24	LCA-100-24V	
Flexi-Light Max	Static White	24	2.6	62.4	2-Way (JWPF), 2000mm	HLG80H-24	PSU-PWM-90-24	LCA-100-24V	
Lumaera 19	Static White	6	9.6	57.6	2-Way (JWPF), 2000mm	HLG80H-24	PSU-PWM-60-24	LCA-60-24V	
	Static White	10	4.8	48	2-Way (JWPF), 2000mm	HLG80H-24	PSU-PWM-60-24	LCA-60-24V	
	Static White	15	4.8	72	2-Way (JWPF), 2000mm	HLG80H-24	PSU-PWM-90-24	LCA-100-24V	
	Tunable White	15	4.8	72	3-Way (JWPF), 2000mm			HLG80H-24 + LIN220D	HLG80H-24 + Hybrid Drive 6
	RGB	15	4.8	72	4-Way (JWPF), 2000mm				HLG80H-24 + Hybrid Drive 6
	RGB Dynamic	15	4.8	72	3-Way (JWPF), 1000mm				HLG80H-24 + Hybrid Drive 6
Lumaera 44	Static White	24	5.0	120	4-Way (JWPS), 2000mm	HLG150H-24	PSU-PWM-120-24	LCA-150-24V	
	Tunable White	24	5.0	120	4-Way (JWPS), 2000mm			HLG150H-24 + LIN220D	HLG150H-24 + Hybrid Drive 6
	RGB	24	5.0	120	4-Way (JWPS), 2000mm				HLG150H-24 + Hybrid Drive 6
	RGB Dynamic	24	5.0	120	4-Way (JWPS), 1000mm				HLG150H-24 + Hybrid Drive 6
	RGBW	24	5.0	120	6-Way (JWPF), 2000mm				HLG150H-24 + Hybrid Drive 6
Lumaera 77	Static White	50	3.0	150	4-Way (JWPS), 2000mm	HLG150H-24		LCA-150-24V	
	Tunable White	50	3.0	150	4-Way (JWPS), 2000mm			HLG150H-24 + LIN220D	HLG150H-24 + Hybrid Drive 6
	RGB	50	3.0	150	4-Way (JWPS), 2000mm				HLG150H-24 + Hybrid Drive 6
	RGB Dynamic	50	3.0	150	4-Way (JWPS), 1000mm				HLG150H-24 + Hybrid Drive 6
	RGBW	50	3.0	150	6-Way (JWPF), 2000mm				HLG150H-24 + Hybrid Drive 6